

# Commercial 95<sup>TM</sup>



**Material Safety Data Sheet**

**Shadecloth Range**

Page 1 of 2  
Rev.2 05/05

## Identification

<b>Product Name</b>	Commercial 95	<b>UN Number</b>	Not Applicable
<b>Other Names</b>	Com95	<b>Hazchem Code</b>	Not Applicable
<b>Product Code</b>	Refer Product Profile	<b>Dangerous Goods Class</b>	Not Applicable
		<b>Poisons Schedule</b>	Not Applicable
<b>Application</b>	Shadecloth for use in architectural tension structures, shade sails etc.		

## Physical Description & Properties

<b>Appearance</b>	Odourless knitted fabric in varying colours	<b>Flashpoint</b>	Not applicable
<b>Melting point</b>	140 °C (284 °F)	<b>Flammability limits</b>	Refer Product Profile
<b>Vapour pressure</b>	Not applicable	<b>Solubility in water</b>	Insoluble
<b>Specific Gravity</b>	0.9		
<b>Other properties</b>			
<b>Ingredients</b>			

<b>Chemical Entity</b>	<b>CAS no.</b>	<b>Proportion</b>
Polyethylene	9002-88-4	~ 95%
Hindered light amine stabiliser	-	~ 1%
Other proprietary pigments and additives	-	~ 4%

## Health Effects

### Exposure

<b>Ingestion</b>	This product is of a solid nature and should not be swallowed.	<b>First Aid</b>	If necessary, seek medical advice.
<b>Eye</b>	May irritate the eye from physical contact.	<b>First Aid</b>	This product is of a solid nature and should not contact the eye. Seek medical advice.
<b>Skin</b>	This fabric may be fabricated using high temperature equipment - beware of molten material.	<b>First Aid</b>	If molten plastic contacts the skin, cool affected area rapidly under cold, clean running water. Do not peel molten plastic from skin. Seek medical advice.
<b>Inhalation</b>	Avoid fumes and or dust generated from, welding, burning or dust from other handling	<b>First Aid</b>	If affected by fumes or dust, remove to a clean well ventilated area. If necessary, seek medical advice

The information set out above has been compiled from supplier reference data including third party Material Safety Data Sheets. Gale Pacific believe that the information is accurate and reliable, though Gale Pacific does not make or give any warranty (other than implied by statute which may not be excluded) with respect to the information. By using this information, the user undertakes not to hold Gale Pacific liable or responsible in any way whatsoever in relation or consequential to such use.

### FOR MORE INFORMATION – PLEASE CONTACT:

Australia	Gale Pacific Ltd. PO Box 892, Braeside, Victoria, 3195	Phone +61 3 9518 3399	Fax +61 3 9518 3398
NZ	Gale Pacific (NZ) Ltd. PO Box 15118, Aranui, Christchurch New Zealand	Phone +64 3 373 9500	Fax +64 3 373 9501
UAE	Gale Pacific FZE. PO Box 17696, Jebel Ali, Dubai	Phone +971 4 881 7114	Fax +971 4 881 7167
USA	Gale Pacific Inc. PO Box 951509, Lake Mary, Florida, 32795-1509	Phone +1 407 333 1038	Fax +1 407 333 7716

# Commercial 95<sup>TM</sup>



Material Safety Data Sheet

Shadecloth Range

Page 2 of 2  
Rev.2 05/05

## Precautions For Use

<b>Exposure standards</b>	Not established
<b>Engineering controls</b>	Fabricate in normal well ventilated areas, use additional ventilation or exhaust extraction systems when welding of hot knife cutting.
<b>Personal protection</b>	Use of general purpose protective gloves is recommended (but not essential) when handling fabric. Wash hands after working with fabric.
<b>Flammability</b>	Combustible but of low flammability. Extinguish by using water spray or extinguisher foam.
<b>Environment</b>	Not hazardous to water. May not break down readily when exposed to microbial attack during landfill disposal.

## Storage Requirements

<b>Storage</b>	Store in a cool dry area away from direct sunlight, halogens and highly acidic substances.
<b>Handling &amp; transport</b>	Use caution when loading and unloading fabric from vehicles. Refer to Product Profile for approximate roll weights.
<b>Spills &amp; Disposal</b>	The product is solid and therefore not subject to spillage. Incinerate under controlled conditions according to local regulations or dispose as an inert solid in a land fill according to local regulations.
<b>Fire &amp; Explosion</b>	The product may accumulate static charges which may cause an incendiary electrical discharge. Thermal decomposition temperature is approximately 280-300°C (536-572°F) combustion may produce carbon dioxide, carbon monoxide, oxides of nitrogen and sulphur as well as small quantities of other organic chemicals.

## OTHER INFORMATION

The resins and additives used in the material are not suitable for food contact.

## CONTACT POINT

Trent Rowe – Marketing Manager – Commercial Fabrics, Gale Pacific Ltd Melbourne.  
Telephone: (03) 9518 3333.

The information set out above has been compiled from supplier reference data including third party Material Safety Data Sheets. Gale Pacific believe that the information is accurate and reliable, though Gale Pacific does not make or give any warranty (other than implied by statute which may not be excluded) with respect to the information. By using this information, the user undertakes not to hold Gale Pacific liable or responsible in any way whatsoever in relation or consequential to such use.

### FOR MORE INFORMATION – PLEASE CONTACT:

Australia	Gale Pacific Ltd. PO Box 892, Braeside, Victoria, 3195	Phone +61 3 9518 3399	Fax +61 3 9518 3398
NZ	Gale Pacific (NZ) Ltd. PO Box 15118, Aranui, Christchurch New Zealand	Phone +64 3 373 9500	Fax +64 3 373 9501
UAE	Gale Pacific FZE. PO Box 17696, Jebel Ali, Dubai	Phone +971 4 881 7114	Fax +971 4 881 7167
USA	Gale Pacific Inc. PO Box 951509, Lake Mary, Florida, 32795-1509	Phone +1 407 333 1038	Fax +1 407 333 7716