

Test Report No. AJFS1909008705FF Date: SEP.09, 2019 Page 1 of 3

## **GALE PACIFIC SPECIAL TEXTILES (NINGBO) LTD**

NO.777 HENSAN-W ROAD, BEILUN, NINGBO

The following sample(s) was / were submitted and identified on behalf of the client. SGS is not responsible for the authenticity, integrity and results of the data and information and / or the validity of the conclusion. results apply to the sample as received.

Sample Description: COMMERCIAL DUALSHADE 350 MACAW

Color: MACAW
Density: 350

Composition: HDPE Style/Item No.: /

#### **Test Requested:**

Determine the flame resistance in accordance with test method 1 of NFPA 701:2015 Standard Methods of Fire Tests for Flame Propagation of Textiles and Films

Test Results: -- See attached sheet --

Conclusion: The tested sample "As received" meets the requirements of Test Method 1 of NFPA

701:2015.

### **Test Period:**

Sample Receiving Date : SEP.02, 2019

Test Performing Date : SEP.02, 2019 TO SEP.06, 2019

Signed for and on behalf of SGS-CSTC Co., Ltd. Anji Branch

Allen Zou Lab Manager





# **Test Report**

No. AJFS1909008705FF

Date: SEP.09, 2019

Page 2 of 3

#### I. Test Conducted

This test was conducted in accordance with test method 1 of NFPA 701:2015 Standard Methods of Fire Tests for Flame Propagation of Textiles and Films.

#### II. Details of tested sample

Sample description / Color	Fabric / Macaw
Area density	About 330 g/m <sup>2</sup>
Products configuration	Single Layer
Size of sample *	150mm × 400mm
Exposed surface	Face surface

<sup>\*</sup> With the length parallel to the lengthwise direction of the material

### III. Conditioning and cleaning procedure

Cleaning procedure: none

Prior to testing, the sample was:

[ ] Dried in oven at 105°C±3°C for 30 minutes.

[  $\sqrt{\ }$  ] Conditioned at 20°C±5°C for 24 hours.

#### IV. Test results

Specimen No.	Mass before test (g)	Mass after test (g)	Mass loss (%)	After flame time (s)	Burning time on floor (s)
1	20.20	20.05	0.74	0	0
2	20.31	19.70	3.00	8.2	0
3	20.43	20.25	0.88	0	0
4	20.12	19.59	2.63	0	0
5	20.92	20.72	0.96	0	0
6	20.48	20.35	0.63	0	0
7	20.35	19.93	2.06	0	0
8	20.46	19.88	2.83	3.7	1.5
9	20.58	20.10	2.33	0	0
10	20.21	19.26	4.70	17.2	4.1
Mean	20.41	19.98	2.08	2.9	0.6

SD =1.3 3SD =3.9 Mean + 3SD =5.98

SD - Standards deviation

To be continued....



Inless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed werleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions, aspx and, for electronic format documents, ubject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-en-Document.aspx. attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is divised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of client's instructions, if any. The Company's sole responsibility is to its Client and this document does not excentrate parties to a ransaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or peparance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the esuits shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

No. 301, Sunlight Road, 2 Block, Sunlight Industry Zone, Anji County, Zhejjang Province, China 313300 t (86-572) 5018825 f (86-572) 5018829 www.sgsgroup.com.cn 中国·浙江·安吉县阳光工业园二区阳光大道301号 邮编:313300 t (86-572) 5018825 f (86-572) 5018829 e sgs.china@sgs.com



# Test Report No. AJFS1909008705FF Date: SEP.09, 2019 Page 3 of 3

#### **Observations:**

Vigorousness of burning	No
Material molten dripping	Yes
Odor smoke	Yes

#### Criteria for test method 1 (Chapter 10):

- 1. Fragments or residues of specimens that fall to the floor of the test chamber shall not continue to burn for more than an average of 2 seconds per specimen for the sample of 10 specimens.
- 2. The average weight loss of the 10 specimens in a sample shall be 40 percent or less.
- 3. No individual specimen's percent mass loss shall deviate more than 3 standard deviations from the mean for the 10 specimens.
- 4. When a retest is required, no individual specimen's percent mass loss in the second set of specimens shall deviate from the mean value by more than 3 standard deviations calculated for the second set.
- 5. When a sample does not demonstrate passing performance in accordance with all of the conditions indicated above, the material shall be recorded as having failed Test Method 1.

**Statement:** This declaration of conformity is only based on the result of this laboratory activity, the impact of the uncertainty of the results was not included.

### **Photo Appendix:**



SGS authenticate the photo on original report only

\*\*\* End of Report \*\*\*

中国·浙江·安吉县阳光工业园二区阳光大道301号



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx.and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions-And-Conditions-And-Con

1443, or email: CN.Doccheck@sgs.com

No. 301, Sunlight Road, 2 Block, Sunlight Industry Zone, Anij County, Zhejjang Province, China 313300 t (86-572) 5018825 f (86-572) 5018829 www.sgsgroup.com.cn

邮编:313300 t (86-572) 5018825 f (86-572) 5018829 e sgs.china@sgs.com